

MIAMI-DADE COUNTY, FLORIDA METRO-DADE FLAGLER BUILDING 140 WEST FLAGLER STREET, SUITE 1603 MIAMI, FLORIDA 33130-1563 (305) 375-2901 FAX (305) 375-2908

NOTICE OF ACCEPTANCE (NOA)

PGT Industries 1070 Technology Drive Nokomis, FL 34275

Scope:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed by Miami-Dade County Product Control Division and accepted by the Board of Rules and Appeals (BORA) to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Division (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. BORA reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Division that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the Florida Building Code, including the High Velocity Hurricane Zone.

DESCRIPTION: Series "PW-701" Aluminum Picture Window-LMI

APPROVAL DOCUMENT: Drawing No. **4259-4**, titled "Aluminum Picture Window, Impact", sheets 1 through 10 of 10, prepared by manufacturer, dated 7/14/03, with revision "A", dated 12/15/03, signed and sealed by Robert L. Clark, P.E., bearing the Miami-Dade County Product Control Approval stamp with the Notice of Acceptance number and approval date by the Miami-Dade County Product Control Division.

MISSILE IMPACT RATING: Large and Small Missile Impact

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA consists of this page 1 and evidence pages E-1 and E-2, as well as approval document mentioned above.

The submitted documentation was reviewed by Theodore Berman, P.E.

NOA No 03-1105.01 Expiration Date: February 19, 2009 Approval Date: February 19, 2004 Page 1



PGT Industries

NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

A. DRAWINGS

- 1. Manufacturer's die drawings and sections.
- 2. Drawing No. 4259-4, titled "Aluminum Picture Window, Impact", sheets 1 through 10 of 10, prepared by manufacturer, dated 7/14/03, with revision "A" dated 12/15/03, signed and sealed by Robert L. Clark, P.E.

B. TESTS

- 1. Test reports on 1) Air Infiltration Test, per FBC, TAS 202-94
 - 2) Uniform Static Air Pressure Test, Loading per FBC, TAS 202-94
 - 3) Water Resistance Test, per FBC, TAS 202-94
 - 4) Large Missile Impact Test per FBC, TAS 201-94
 - 5) Cyclic Wind Pressure Loading per FBC, TAS 203-94

along with marked-up drawings and installation diagram of an aluminum picture window, prepared by Fenestration Testing Laboratory, Inc., Test Report No. **FTL-3835**, dated 07/18/03, signed and sealed by Joseph Chan, P.E.

- 2. Test reports on 1) Air Infiltration Test, per FBC, TAS 202-94
 - 2) Uniform Static Air Pressure Test, Loading per FBC, TAS 202-94
 - 3) Water Resistance Test, per FBC, TAS 202-94
 - 4) Large Missile Impact Test per FBC, TAS 201-94
 - 5) Cyclic Wind Pressure Loading per FBC, TAS 203-94

along with marked-up drawings and installation diagram of an aluminum picture window, prepared by Fenestration Testing Laboratory, Inc., Test Report No. FTL-3850, dated 07/31/03, signed and sealed by Joseph Chan, P.E.

C. CALCULATIONS

1. Anchor Calculations, ASTM-E1300-98, and structural analysis, prepared by manufacturer, dated 10/31/03, signed and sealed by Robert L. Clark, P.E.

D. QUALITY ASSURANCE

1. Miami Dade Building Code Compliance Office (BCCO).

E. MATERIAL CERTIFICATIONS

- 1. Notice of Acceptance No. **02-0828.15** issued to E.I. DuPont DeNemours for "DuPont Butacite PVB Material" dated 11/21/02, expiring on 12/11/05.
- 2. Notice of Acceptance No. **01-0205.02** issued to Solutia, Inc. for "Saflex / Keepsafe Maximum" dated 5/17/01, expiring on 5/21/06.

Theodore Berman, P.E.

Deputy Director, Product Control Division

NOA No 03-1105.01

Expiration Date: February 19, 2009 Approval Date: February 19, 2004

PGT Industries

NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

F. STATEMENTS

- 1. Laboratory compliance letter for Test Report no. FTL-3835, issued by Fenestration Testing Laboratory, Inc., dated 08/25/03, signed and sealed by Joseph Chan, P.E.
- 2. Laboratory compliance letter for Test Report no. **FTL-3850**, issued by Fenestration Testing Laboratory, Inc., dated 08/21/03, signed and sealed by Joseph Chan, P.E.

G. OTHER

1. Letter from the consultant stating that the product is in compliance with the Florida Building Code (FBC).

Clevan Loman Theodore Berman, P.E.

Deputy Director, Product Control Division NOA No 03-1105.01

Expiration Date: February 19, 2009 Approval Date: February 19, 2004

NOTES: LARGE MISSILE WINDOWS

- 1. GLAZING OPTIONS:
 - A. 7/16" LAMINATED GLASS COMPRISED OF (1) LITE OF 3/16" ANNEALED GLASS AND (1) LITE OF 3/16" HEAT STRENGTHENED GLASS WITH AN .090 INTERLAYER OF DUPONT BUTACITE OR SAFLEX KEEPSAFE MAXIMUM PVB.
 - B. 7/16" LAMINATED GLASS COMPRISED OF (2) LITES OF 3/16" HEAT STRENGTHENED GLASS GLASS WITH AN .090 INTERLAYER OF DUPONT BUTACITE OR SAFLEX KEEPSAFE MAXIMUM PVB.
 - C. 1 1/16" LAMI I.G. GLASS COMPRISED OF (1) LITE OF 3/16" HEAT STRENGTHENED GLASS, A 7/16" AIRSPACE AND 7/16" LAMINATED GLASS WHICH IS COMPRISED OF (1) LITE OF 3/16" ANNEALED GLASS AND (1) LITE OF 3/16" HEAT STRENGTHENED GLASS WITH AN .090 INTERLAYER OF DUPONT BUTACITE OR SAFLEX KEEPSAFE MAXIMUM PVB.
 - D. 1 1/16" LAMI I.G. GLASS COMPRISED OF (1) LITE OF 3/16" HEAT STRENGTHENED GLASS, A 7/16" AIRSPACE AND 7/16" LAMINATED GLASS WHICH IS COMPRISED OF (2) LITES OF 3/16" HEAT STRENGTHENED GLASS WITH AN .090 INTERLAYER OF DUPONT BUTACITE OR SAFLEX KEEPSAFE MAXIMUM PVB.
- DESIGN PRESSURE RATINGS: (FLANGED SEE SHEET 5, TABLE 1 AND INTEGRAL FIN SEE SHEET 6, TABLE 2)
 A. NEGATIVE DESIGN LOADS BASED ON TESTED PRESSURE AND GLASS TABLES ASTM E 1300-98 (AND ASTM E 1300-94 OUTSIDE MIAMI-DADE COUNTY).
 - B. POSITIVE DESIGN LOADS BASED ON WATER TEST PRESSURE AND GLASS TABLES ASTM E 1300-98 (AND ASTM E 1300-94 OUTSIDE MIAMI-DADE COUNTY).
 - C. DESIGN PRESSURES UNDER 40 P.S.F. NOT APPLICABLE IN MIAMI-DADE COUNTY.
- 3. FLANGED UNIT ANCHORAGE: SINGLE ROW OF FASTENERS LOCATED AS FOLLOWS: (SEE SHEET 10, DETAILS C, D & E)

HEAD & SILL: MAX. 8 1/2" FROM CORNERS

MAX. 11" O.C.

JAMBS:

A MAX. 8 1/2" FROM CORNERS

MAX. 11" O.C.

(DESIGN PRESSURE LIMITED TO 60 P.S.F. WHEN ANCHORING WITH #12 SCREWS)

4. INTEGRAL FIN UNIT ANCHORAGE WITH NAILS: SINGLE ROW OF .130 DIA. x 2 1/2" LG. NAILS AS FOLLOWS: (SEE SHEET 10, DETAIL A)

HEAD & SILL: AT EACH CORNER

MAX. 5" O.C.

JAMBS:

AT EACH CORNER

MAX. 5" O.C.

5. INTEGRAL FIN UNIT ANCHORAGE WITH #12 SCREWS: SINGLE RCW OF SCREWS AS FOLLOWS: (SEE SHEET 10, DETAIL B)

HEAD & SILL: MAX. 8 1/2" FROM CORNERS

MAX. 11" O.C.

JAMBS:

MAX. 8 1/2" FROM CORNERS

MAX. 11" O.C.

(DESIGN PRESSURE LIMITED TO 60 P.S.F. WHEN ANCHORING WITH #12 SCREWS)

- 6. SHUTTER REQUIREMENT: NONE REQUIRED
- 7. NARROW JOINT SEALANT IS USED ON ALL FOUR CORNERS OF THE FRAME.
- 8. REFERENCE TEST REPORTS: FTL-3835 & FTL-3850

novou by.	Dato.	INCVISIONS.			
Revsd By:	Date:	Revisions:		1070 TECHNOLOGY DRIVE NOKOMIS, FL 34275	P
Revsd By:	Date:	Revisions:		1	
F.K.	12/15/03	Α	REDUCE ANCHOR SPACING	P.O. BOX 1529	
Drawn By:	Date:	Checked By:	Date:	NOKOMIS, FL 34274	1
F.K.	7/14/03		` 		



NOTES & TABLE OF CONTENTS

ALUMINUM PICTURE WINDOW, IMPACT

Model: Scale: Sheet: Drawing No. 4259-4


SHEET
GENERAL NOTES 1
GLAZING DETAILS 2
ELEVATIONS, FLANGED 3
ELEVATIONS, INTEGRAL FIN 4
DESIGN PRESSURES FLANGED 5
DESIGN PRESSURES FINNED 6
SECTIONS, FLANGED 7
CORNER ASS'Y, FLANGED 7
SECTIONS, INTEGRAL FIN 8
CORNER ASS'Y, INTEGRAL FIN 8
EXTRUSION PROFILES 9
PARTS LIST 9
ANCHORAGE 1 & 10

NOA DRAWING TABLE OF CONTENTS


Approved as complying with the Ploride Building Code
Date 02/19/10/4
NOA# 03-1105.01
Minari Dade Product Code
Division
Division

12/14/63

Robert L. Clark, P.E. PE #39712 Structural








FULL CIRCLE MAX. SIZE = 60" DIA.


OR MAX. AREA = 19.63 SQ. FT.




MAX. SIZE = 60" BETWEEN FLATS OR MAX. AREA = 20.71 SQ. FT.



MAX. SIZE = 68" X 68" OR MAX. AREA = 25.22 SQ. FT.




MAX. SIZE = 48" X 96" OR MAX. AREA = 30.28 SQ. FT.




FAN MAX. SIZE = 96" X 47" OR MAX. AREA = 24.47 SQ. FT.




EYEBROW MAX. SIZE = 96" X 48" OR MAX. AREA = 31.99 SQ. FT.






TRAPEZOID




HALF CIRCLE MAX. SIZE = 96" X 48" OR MAX. AREA = 25.13 SQ. FT.



RECTANGLE

MAX. SIZE = 48" X 96" OR MAX. AREA = 32.00 SQ. FT.



MAX. SIZE = 48" X 96" OR MAX. AREA = 31.99 SQ. FT.

NOTE:

FOR ANCHORAGE INFORMATION SEE NOTE 3, SHEET 1 AND SHEET 10, DETAILS C, D & E.


evsd By:	Date:	Revisions:			
evsd By:	Date:	Revisions:			1070 TECHNOLOGY DRIVE NOKOMIS, FL 34275
evsd By: K.	Date: 12/15/03	Revisions:	NO CHANGE	THIS SHEET	P.O. BOX 1529
rawn By: F.K.	Date: 7/14/03	Checked By:	Date:		 NOKOMIS, FL 34274



I	Description: FLANGED	ELEV	ATIO	DN	S	
•	Title: ALUMINUN	1 PICT	ruri	ΕV	VINE	OOW, IMPACT
,	Series/Model:	Scale:	Sheet:			Drawing No.
1	PW-701	NTS	3	of	10	4259-4

Robert L. Clark, P.E. PE #39712

Structural



1070 TECHNOLOGY DRIVE NOKOMIS, FL 34275

P.O. BOX 1529

NOKOMIS, FL 34274

Visibly Better

PW-701

12/15/03

Drawn By: Date: 7/14/03

A NO CHANGE THIS SHEET

4259-4

INTEGRAL FIN ELEVATIONS

ALUMINUM PICTURE WINDOW, IMPACT

NTS | 4 of 10

PE #39712 Structural

ARCH.

COMPARA	TIVE A	NALYSIS	TABLE	1.	··.	- Sex.							
· · ·	 		LAMINA		SS (3/16	"A090.	3/16HS)					F	TL-3835
GLASS 1	VDE.		LAMINA)					TL-3835
GLASS I	IFE.		C. 1 1/16" LAMI I.G., 3/16HS, 7/16" SPACE, 7/16" LAMI (3/16A, .090, 3/16" HS)										TL-3850
					., 3/16HS, 7/16" SPACE, 7/16" LAMI (3/16HS, .090, 3/16" HS) FTL-3850								
WINDOW				-			WINDOV	V HEIGH	Γ				
WIDTH		28.	500	34.	000	39.	500	45.	000	46.	500	48.	000
49.000	A&C	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0
	B&D	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0
AREA	SQ.FT.		98		569	13.	441	15.	313	15.	823	16.	333
54.500	A&C	80.0	-80.0	80.0	-80.0	80.0	-80.0	76.7	-76.7	74.0	-75.2	74.0	-74.0
	B&D	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0
AREA SQ.FT					868		950	17.			599	18.	167
60.000	A&C	80.0	-80.0	80.0	-80.0	74.0	-74.0	69.9	-69.9	67.2	-68.6	67.2	-67.2
4054	B&D	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0
AREA	SQ.FT.				167	19	458	18.750 19.375		20.000			
65.500	A&C	80.0	-80.0	80.0	-80.0	68.5	-68.5	63.5	-63.5	61.3	-62.3	61.3	-61.3
ADEA	B&D	80.0	-80.0 964	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0
AREA	SQ.FT.				465		967	20.4			151	21.	
71.000	A&C B&D	80.0	-80.0	79.4	-79.4	63.7	-63.7	57.9	-57.9	56.1	-57.1	56.1	-56.1
AREA		80.0	-80.0	80.0 16.1	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0
ANEA	A&C	14.052		76.8		19.476		22.188 22.927			23.667		
76.500	B&D	80.0 80.0	-80.0 -80.0	80.0	-76.8 -80.0	59.7	-59.7	52.8	-52.8	51.9	-52.1	51.9	-51.9
AREA		15.			263	80.0 20.5	-80.0	80.0 23.9	-80.0	80.0	-80.0 703	80.0	-80.0
	A&C	80.0	-80.0	74.1	-74.1	56.5	-56.5	48.3	-48.3	47.6	-48.0	25.3	
82.000	B&D	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	- 4 6.0	47.6 80.0	-47.6 -80.0
AREA	SQ.FT.	16.2		19.3			493	25.6		26.4		27.	
	A&C	80.0	-80.0	70.7	-70.7	53.6	-53.6	43.6	-43.6	43.4	-43.2	43.4	-43.4
87.500	B&D	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0
AREA	SQ.FT.	17.3	318	20.6		24.0		27.3		28.2		29.1	
93.000	A&C	80.0	-80.0	69.1	-69.1	51.4	-51.4	42.5	-42.5	40.7	-41.0	40.7	-40.7
30.000	B&D	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0	79.4	-79.4
AREA		18.4	406	21.9	958	25.3	510	29.0	063	30.0	031	31.0	000
96.000	A&C	80.0	-80.0	68.8	-68.8	50.4	-50.4	41.6	-41.6	39.4	-40.1	39.4	-39.4
	B&D	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0	76.6	-76.6
AREA S	SQ.FT.	19.0	000	22.6	667	26.3	333	30.0	000	31.0	000	32.0	000
NOTES: TABLE 1 PRI	ESSURES	ARF BASE	D ON THE I	ARGEST T	ESTED SIZE	E RECTANO	SHI AD WIN		ODED WITE	1 4//# TADO		או סטבפטייי	DEC ADE L''

SSURES ARE BASED ON THE LARGEST TESTED SIZE RECTANGULAR WINDOW ANCHORED WITH 1/4" TAPCONS. DESIGN PRESSURES ARE LIMITED TO +/-60 P.S.F. WHEN ANCHORING WITH #12 SCREWS.

2. ALL MAXIMUM SIZES SHOWN ON SHEET 3 ARE QUALIFIED TO THE PRESSURE OF A 32 SQ. FT. UNIT IN TABLE 1.

3. ALL SHAPES LESS THAN THE MAXIMUM SIZE, QUALIFY TO PRESSURE FOR THE MAXIMUM SIZE LISTED IN TABLE 1, OR TO THE PRESSURE FOR THE SMALLEST RECTANGULAR SIZE IN TABLE 1, WHICH THEIR OVERALL WIDTH AND HEIGHT DIMENSIONS COMPLETELY FIT WITHIN.


Revsd By:	Date:	Devisions			CINO OCIVIL EL
nevsu by.	Date.	Revisions:			
		i		l	
		l .			
Revsd By:	Date:	Revisions:	,	1070 TECHNOLOGY DRIVE	
		1,10,10,10,10,			
				NOKOMIS. FL 34275	
Revsd By:	D-4	5 / 1		110/10/11/0, 12 0 12/0	
nevsu by:	Date:	Revisions:	·		
F.K.	12/15/03	Ι Λ	CHANGE NOTE 1 ANCHORING WITH #12 SCREWS	P.O. BOX 1529	
1 dt.	12/13/03	^1	CHANGE NOTE TANCHURING WITH #12 SCREWS	F.O. BOX 1029	
Drawn By:	Date:	Checked By:	Date:	NOKOMIS. FL 34274	Visibly B
		Chooned by.	Date.	710710711071207274	VISIDIY D
F.K.	7/14/03				•
		L			



FLANGED UNIT DESIGN PRESSURES

ALUMINUM PICTURE WINDOW, IMPACT

NTS 5 of 10 4259-4



PE #39712

COMPARA	ATIVE A	NALYSIS	TABLE	2.									
			LAMINA ³		SS (3/16 ^t	"A090.	3/16HS)					F	-TL-3835
GLASS .	TVDE		LAMINA)					TL-3835
GLASS	IIPE.								090. 3/	16" HS)			TL-3850
	_	D. 1 1/16	I 1/16" LAMI I.G., 3/16HS, 7/16" SPACE, 7/16" LAMI (3/16A, .090, 3/16" HS) FTL-3850 I 1/16" LAMI I.G., 3/16HS, 7/16" SPACE, 7/16" LAMI (3/16HS, .090, 3/16" HS) FTL-3850										
WINDOW					WINDOW HEIGHT								
WIDTH		28.	500	34.	000	39.	500	45.	000	46.	500	48.	000
49.000	A&C	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0	79.4	-80.0	79.4	-79.4
45.000	B&D	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0
AREA	SQ.FT.	9.6	598	11.	569	13.	441	15.	313	15.	823	16.	333
54.500	A&C	80.0	-80.0	80.0	-80.0	78.9	-78.9	74.3	-74.3	71.9	-73.1	71.9	-71.9
04.000	B&D	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0
AREA	SQ.FT.				868		950		031	17.	599	18.	167
60.000	A&C	80.0	-80.0	80.0	-80.0	72.2	-72.2	67.8	-67.8	65.0	-66.4	65.0	-65.0
	B&D	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0
AREA SQ.FT					167		6.458 18.750 19.37		375	20.000			
65.500	A&C	80.0	-80.0	78.9	-78.9	65.5	-65.5	61.7	-61.7	59.6	-60.7	59.6	-59.6
	B&D	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0
AREA SQ.FT		12.964			465		967		469	21.		21.	833
71.000	A&C	80.0	-80.0	75.3	-75.3	61.1	-61.1	56.4	-56.4	54.6	-55.5	54.6	-54.6
1554	B&D	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0
AREA	SQ.FT.		052		764	71	476	22.			927		667
76.500	A&C	80.0	-80.0	72.6	-72.6	57.1	-57.1	51.5	-51.5	51.0	-51.3	51.0	-51.0
4554	B&D	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0
AREA	SQ.FT.		141	18.063		20.984		23.9			703	25.	
82.000	A&C	80.0	-80.0	69.4	-69.4	53.8	-53.8	47.2	-47.2	46.6	-46.9	46.6	-46.6
4054	B&D	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0
AREA	SQ.FT.		229	19.3		22.4		25.0			479		333
87.500	A&C B&D	80.0	-80.0	66.4	-66.4	51.0	-51.0	42.6	-42.6	43.1	-42.7	43.1	-43.1
ADEA	SQ.FT.	80.0 17.3	-80.0	80.0 20.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	-80.0
	A&C	80.0	-80.0	65.0		24.0		27.3			255	29.	
93.000	B&D	80.0	-80.0	80.0	-65.0 -80.0	48.9	-48.9	41.2	-41.2	40.4	-40.2	40.4	-40.4
ΔRFΔ	SQ.FT.	18.4		21.9		80.0 25.	-80.0 510	80.0 29.0	-80.0	79.7 <i>30.</i> 0	-79.7	76.0	-76.0
	A&C	80.0	-80.0	63.9	-63.9	48.0	-48.0	40.2	-40.2	39.0		31.0	
96.000	B&D	80.0	-80.0	80.0	-80.0	80.0	-80.0	80.0	- 4 0.2 -80.0	76.9	-38.9 -76.9	39.0 73.1	-39.0 73.1
ARFA	SQ.FT.	19.0		22.6		26.3		30.0		31.0		73.1 32.0	-73.1
NOTES:	- Q., 1.					20.0		00.0	,00	01.0		J2.(<i>7</i> 00
1. TABLE 2 PR	RESSURES	ARF BASE	D ON THE I	ARGEST T	ESTED SIZE	E RECTANG	HIM QA III		ODED WITL	1 1//" TADO	ONE DEGIC	N DDECCH	

1. TABLE 2 PRESSURES ARE BASED ON THE LARGEST TESTED SIZE RECTANGULAR WINDOW ANCHORED WITH 1/4" TAPCONS. DESIGN PRESSURES ARE LIMITED TO +/-60 P.S.F. WHEN ANCHORING WITH #12 SCREWS.

2. ALL MAXIMUM SIZES SHOWN ON SHEET 4 ARE QUALIFIED TO THE PRESSURE OF A 32 SQ. FT. UNIT IN TABLE 2.

3. ALL SHAPES LESS THAN THE MAXIMUM SIZE, QUALIFY TO PRESSURE FOR THE MAXIMUM SIZE LISTED IN TABLE 2, OR TO THE PRESSURE FOR THE SMALLEST RECTANGULAR SIZE IN TABLE 2, WHICH THEIR OVERALL WIDTH AND HEIGHT DIMENSIONS COMPLETELY FIT WITHIN.


levsd By:	Date:	Revisions:			
levsd By:	Date:	Revisions:			 1070 TECHNOLOGY DRIVE NOKOMIS, FL 34275
evsd By: F.K.	Date: 12/15/03	Revisions:	CHANGE NO	TE 1 ANCHORING WITH #12 SCREWS	 P.O. BOX 1529
rawn By: F.K.	Date: 7/14/03	Checked By:	Date:		NOKOMIS, FL 34274



INTEGRAL FIN UNIT DESIGN PRESSURES


ALUMINUM PICTURE WINDOW, IMPACT


| Series/Model: | Scale: | Sheet: | Drawing No. | Rev. | PW-701 | NTS | 6 of 10 | 4259-4 | A



t Illast

Robert L. Clark, P.E. PE #39712 Structural





ITEM	DWG NO.	PART #	DESCRIPTION
1	4256A	64256	INTEGRAL FIN FRAME HEAD, SILL & JAMB
2	4253	64253	FLANGED FRAME HEAD, SILL & JAMB
7	1155	781PQX	#8 X 1 QUAD PN SMS STAINLESS STEEL
8			SCHNEE-MOREHEAD SM5504 ACRYL-R NARROW JOINT SEALANT OR EQUAL
10	4255	64255	7/16 LAMI GLASS BEAD
11	4254	64254	1 1/16 LAMI I.G. GLASS BEAD
12	1224	6TP247	VINYL BULB WEATHERSTRIP (THICK)
13	4224		INSTALLATION FASTENER COVER
14			DOW CORNING 899 GLAZING SEALANT
15			DOW CORNING 995 SILICONE STRUCTURAL SEALANT, BLACK
17			7/16" LAMI GLASS: 3/16" ANNEALED090 DUPONT BUTACITE OR SAFLEX KEEPSAFE MAXIMUM PVB INTERLAYER - 3/16" HEAT STRENGTHENED
18			1 1/16" LAMI I.G. GLASS: 3/16" HEAT STRENGTHENED OUTBOARD - 7/16" AIRSPACE - 3/16" ANNEALED090 DUPONT BUTACITE OR SAFLEX KEEPSAFE MAXIMUM PVB INTERLAYER - 3/16" HEAT STRENGTHENED
20	4262	64262	ARCHITECTURAL CORNER KEY
21			7/16" LAMI GLASS: 3/16" HEAT STRENGTHENED090 DUPONT BUTACITE OR SAFLEX KEEPSAFE MAXIMUM PVB INTERLAYER - 3/16" HEAT STRENGTHENED
22			1 1/16" LAMI I.G. GLASS: 3/16" HEAT STRENGTHENED OUTBOARD - 7/16" AIRSPACE - 3/16" HEAT STRENGTHENED090 DUPONT BUTACITE OR SAFLEX KEEPSAFE MAXIMUM PVB INTERLAYER - 3/16" HEAT STRENGTHENED


- .970" -

ITEM 10,


7/16 LAMI GLASS BEAD

.975"

.050"




<u>ITEM 11,</u> 1 1/16 LAMI I.G. GLASS BEAD




ITEM 1, INTEGRAL FIN FRAME

MAT'L: 6063-T5 DWG NO. 4256A




ITEM 2, FLANGED FRAME

_							•• —,	. –	, ,, , ,	
			L: 6063-T5 NO. 4255	MAT'L: 6063-T5 DWG NO. 4254					T'L: 606 'G NO.	
vsd By:	Date:	Revisions:				Description:				
vsd By:	Date:	Revisions:		1070 TECHNOLOGY DRIVE	DAT	EXTRUSIC	N PR	OFIL	.ES & F	PARTS LIST
	 	<u> </u>		NOKOMIS, FL 34275		Title:				
vsd By: K.	12/15/03	Revisions:	NO CHANGE THIS SHEET	P.O. BOX 1529		ALUMINUN	<u> 1 PICT</u>	<i>URL</i>	E WIND	DOW, IMPAC
awn By:	Date:	Checked By	Date:	NOKOMIŚ, FL 34274	Visibly Better	Series/Model;	Scale:	Sheet:		Drawing No.
F.K.	7/14/03				VISIDIY Decter	PW-701	NTS	9	of 10	4259-4



Robert L. Clark, P.E. PE #39712 Structural



Revsd By:	Date:	Revisions:				Description:			
Revsd By:	Date:	Revisions:		1070 TECHNOLOGY DRIVE NOKOMIS, FL 34275	POT	ANCHORAG	SE - HEAD, SILL	L AND JAMBS	
Revsd By: F.K.	Date: 12/15/03	Revisions:	CHANGE NOTE 1 AND FASTENER SPACING	P.O. BOX 1529		ALUMINUM	PICTURE WINL	DOW, IMPACT	
Drawn By: F.K.	Date: 7/14/03	Checked By:		NOKOMIS, FL 34274	Visibly Better	Series/Model: Sc PW-701	ale: Sheet: NTS 10 of 10	Drawing No. 4259-4	Rev:

Robert L. Clark, P.E. PE #39712